


TPPPL-NHS-WL DATA SHEET

NHS-WL



Product Description

TPPPL - NHS - WL is transparent, high gloss, corona treated designed for reel fed wrap around labelling applications. It is designed for optimized performance on the most demanding labelling machines.

Key Features

- Outstanding optical properties
- Excellent ink adhesion
- Good tear & split resistance
- Good mechanical properties
- Good anti-static and slip properties
- Good mould resistance
- Excellent hot melt anchorage

TECHNICAL SPECIFICATION

Properties	Unit	Method	Typical Values (NHS-WL)			
Physical Properties						
Nominal Thickness	μ	TPPPL	30	35	38	40
Grammage	gm/m ²	TPPPL	27.3	31.85	34.6	36.4
Density	Gm/cc	TPPPL	0.905 - 0.910			
Yield	m²/kg	TPPPL	36.6	31.4	28.9	27.5
Optical Properties						
Haze (Max)	%	ASTM D 1003	1.5	1.8	1.9	2.0
Gloss @ 45° (Min)	-	ASTM D 2457	90			
Surface Properties						
Wetting Tension (Min)	Dyne/cm	ASTM D 2578	38			
Dynamic Coefficient of Friction (NT/NT)	-	ASTM D 1894	0.40			
Mechanical Properties						
Tensile Strength (at Break) (Min)	N/mm²	ASTM D 882 MD TD	150 280			
Elongation (at Break) (Max)	%	ASTM D 882 MD TD	17 0 50			
Elastic Modulus (Min)	N/mm²	ASTM D 882 MD TD	1900 3200			
Thermal Properties						
Shrinkage@120°C 5 Minutes air (Max)	%	TPPPL MD TD			l.0 l.0	
MD- Machine Direction, TD- Transverse Direction, NT- Non-Treated, RH- Relative Humidity, TPPPL- Tempo Paper Pulp & Packaging Ltd.						



Corona Treatment Indication

TPPPL – NHS-WL can be supplied either with treatment on the inside surface (TI) Outside surface (TO) or treated on both sides (TB). This must be agreed with our sales representative before processing the order.

Roll Size Availability

Film Type	Standard Length (m)	2 x Std. Length	4 x Std. Length	6 x Std. Length	8 x Std. Length
NHS-WL30	2100	4200	8400	12600	16800
NHS-WL 35	1800	3600	7200	10800	14400
NHS-WL 38	1700	3400	6800	10200	13600
	1600	3200	6400	9600	12800

Corresponding Roll's Outer Diameter

Core ID 76 m	m 305 mm	419 mm	588 mm	716 mm	825 mm
Core ID 152 n	nm 337 mm	444 mm	605 mm	730 mm	838 mm

^{*}For availability of roll sizes (multiples of standard length) please refer to the Sales Representative

Legal Statement

Contact your Tempo Customer Service Representative /Sales Representative for potential food contact application compliance (e.g. FDA, NAFDAC) & MSDS. This product is not intended for use in medical applications and should not be used in any such applications. The figures and data provided in this datasheet are consistent with the current state of our knowledge and are intended to provide general information about our products and their applications. They do not constitute a guarantee of any specific product attributes or the suitability of products for specific applications.

For technical enquiries, please contact:					
Sandeep Kumar, Q.A. Manager	1	sandeep.kumar@tempong.com	I	07045745029	

Factory & Sales Office:
Tempo Paper Pulp & Packaging Ltd.
Klm5, Idiroko Road, Behind General Hospital
Ota, Ogun State, Nigeria.
info@tempong.com